

OAS KN8V1 IX

12NC/Fx: 859991558460

GTIN (EAN) code: 8003437938801

DIMENSION		MEASUR	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm	
VIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
VIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mn	
ANN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mn	
Space in front, which is required to install bottom trim	9	mn	
ndicates whether a ventilation opening is needed or not. Default is "N"	Yes		
NALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (wall cabinet)	Rear		
Vinimum space or inbound ventilation (wall cabinet)	0	mn	
Vinimum area for inbound ventilation cavity (wall cabinet)	0	cm	
NALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (wall cabinet)	Rear		
Vinimum space or outbound ventilation (wall cabinet)	0	mm	
Vinimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Vinimum space for inbound ventilation (tall cabinet)	40	mn	
Vinimum area for inbound ventilation cavity (tall cabinet)	150	cm	
TALL CABINET (vent-shaft outgoing)		0	
ndicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
		mn	
		cm	
• • •		0	
	Rear		
		mn	
		cm	
	150	UII	
	Rear		
		mr	
		mm cm ²	
Minimum space for outbound ventilation (tall cabinet) Minimum area for outbound ventilation cavity (tall cabinet) BASE CABINET (vent-shaft incoming) Indicates the position of the freespace for the inbound airflow (base cabinet) Minimum space for inbound ventilation (base cabinet) Minimum area for inbound ventilation cavity (base cabinet) BASE CABINET (vent-shaft outgoing) Indicates the position of the freespace for the outbound airflow (base cabinet) Minimum space for outbound ventilation (base cabinet) Minimum space for outbound ventilation (base cabinet) Minimum area for outbound ventilation cavity (base cabinet) Minimum area for outbound ventilation cavity (base cabinet)	0 150 Rear 40 150 Rear 0 150	n c	

DIMENSION	IEAS	EASURE	
APPLIANCE			
Height of the front	595	mn	
Width of the front	595	mr	
Depth of the front	20	mr	
Maximum depth all protruding elements, e.g. handles, controls	42	mr	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	34	mn	
Projection of front in relation to housing of appliance	20	mn	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	5	mn	
When product panel is missing, set to 0	97	mn	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	460	mn	
Height from bearing area of appliances and lower handle	432	mr	
Frontal handle thickness	25	mr	
Frontal handle width	527	mr	
MIN Height of the product body	570	mr	
MAX Height of the product body	570	mr	
Width of the product body	558	mr	
Depth of the product body	548	mr	
Full depth of product excluding protruding interface elements	570	mr	
-	-	mr	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mr	
Maximum angle when flap door is opened totally	89	mr	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mr	
Lateral projection of opened front at the side where the hinge is fixed	0	mr	
Maximum angle when door is opened totally	0	mr	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	428	mr	
Height from niche to bottom end of freespace for the retrace	525	mr	