

## **AKZM 8660 IX**

12NC/Fx: 852586601100

## GTIN (EAN) code: 8003437832406

DIMENSION	<b>MEAS</b>	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	10	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm <sup>2</sup>
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	_	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>
BASE CABINET (vent-shaft outgoing)	- U	J
Indicates the position of the freespace for the outbound airflow (base cabinet)	_	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>
minimum area for eathering ventulation eavity (vase earlier)	U	Citi

PPLIANCE		
eight of the front	595	mm
dth of the front	595	mm
epth of the front	20	mm
aximum depth all protruding elements, e.g. handles, controls	42	mm
teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees	35	mm
ojection of front in relation to housing of appliance	18	mm
ojection of front in relation to bearing area of the appliance. Taken at minimum height of pliance, if height is adjustable	5	mm
hen product panel is missing, set to 0	95	mm
bace in front, which is required to guarantee full operability. The most protruding part gives this mension	477	mm
eight from bearing area of appliances and lower handle	440	mm
ontal handle thickness	25	mm
ontal handle width	527	mm
N Height of the product body	572	mm
AX Height of the product body	572	mm
dth of the product body	546	mm
epth of the product body	543	mm
Il depth of product excluding protruding interface elements	564	mm
	-	mm
pliance can be used as base for other appliances from the same manufacturer. Default is "No"	No	
ppliance Flap door		
ojection of the opened flap in relation to bearing area	0	mm
aximum angle when flap door is opened totally	89	mm
ppliance Side swing door		
teral projection of front incl. controls when door is opened totaly. At the side where the hinge is bunted	0	mm
teral projection of opened front at the side where the hinge is fixed	0	mm
aximum angle when door is opened totally	0	mm
ppliance other		
epth from front end of the niche to the front end of the freespace of the retrace	345	mm
eight from niche to bottom end of freespace for the retrace	537	mm